



* Standard double glazed unit:
 6mm toughened outer
 16mm argon filled cavity, black warm edge spacer
 6mm toughened soft coat low E inner

GLAZING VISION
 Saw Mills Road
 Diss
 Norfolk
 IP22 4RG
 Tel: +44 (0)333 8000 881
 Fax: +44 (0)333 8000 882
 Email: sales@glazing-vision.co.uk
 Website: www.glazing-vision.co.uk

IT IS GLAZING VISION'S POLICY TO CONTINUOUSLY DEVELOP AND IMPROVE OUR PRODUCTS. AND THEREFORE RESERVE THE RIGHT TO MODIFY OR CHANGE THE DETAIL DESIGN AT OUR DISCRETION AND WITHOUT PRIOR NOTICE. THIS DRAWING IS COPYRIGHT AND THE SOLE PROPERTY OF GLAZING VISION LTD. THE DESIGNS/INFORMATION IT CONTAINS ARE PRIVATE AND CONFIDENTIAL. IT MUST NOT BE COPIED, EXHIBITED OR COMMUNICATED TO THIRD PARTIES FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS ISSUED WITHOUT THEIR WRITTEN PERMISSION.

Third angle projection unless otherwise noted.
 Tolerances:
 Whole numbers = ±1mm
 One decimal place = ±0.5mm
 Two decimal places = ±0.2mm
 Angular = ±0.5 degree
IF IN DOUBT - ASK! DO NOT SCALE
Supplier to deburr & remove sharp corners

Rev	Revision Description	Drawn/Date
I	Kerb top feature offered as optional extra with reference to drawing S0011. Amended view in top right corner	PGW 21/3/2011
H	New Flushglaze extrusion design. Drawing converted to inventor	PGW 13/1/2011

Product: 402 - Flushglaze	Checked By:
Description: Double glaze Flushglaze kerb mount detail	
Materials: See above	Check Date:
Finish: Std = RAL7015 Grey, Matt	
Weight: N/A	Drawn By: JPD
Quantity: N/A	Drawn Date: 01/01/2003
Scale: 1:2 @ A4	Drawing No: 402-ASS-001